



WIRE LIST:

P1	P2
C1	1
C2	2
C3	3
15	5
	10
C5	6
	7
14	8
16	9
7	12
C4	13
8	14
6	15
SHELL	SHELL

NOTE:

1. ALL MATERIALS/PROCESSES ARE ROHS COMPLIANT.

ELECTRONIC TEST CONDITION:
 100% OPEN SHORT & MISWIRE TEST.
 CONDCTIVE RESISTANCE:3Ω /MAX
 INSULATION RESISTANCE:20MΩ /MIN.AT DC 300V

PE BAG	PE BAG:60*90*0.06mm
PVC	MOLDED 45 PVC
SCREW	SCREW #4-40UNC,Ø5.8*23mm NICKEL PLATED
CONN.	HDD 15P FEMALE CONNECTOR SOLDER TYPE CONTACT GOLD
	FLASH.INSULATOR BLACK.NICKEL PLATED FRONT SHELL PLATED SHELL TIN PLATED BACK SHELL
CONN.	DVI 24+5 MALE CONNECTOR SOLDER TYPE CONTACT GOLD FLASH
	INSULATOR WHITE.FRONT NICKEL PLATED BACK TIN PLATED BACK SHELL
CABLE	HOOK UP WIRE:UL1061 28AWG*1C TINNED COPPER WIRE,
	INSULATION:YELLOW PVC OD=0.9±0.1mm.L=22±1mm.
CABLE	HOOK UP WIRE:UL1061 28AWG*1C TINNED COPPER WIRE,
	INSULATION:BLACK PVC OD=0.9±0.1mm.L=17±1mm.
NAME	DESCRIPTION

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
	APPD. 核准 Betty	TOLERANCE 容許公差 .0 ± 0.20 .00 ± 0.15 ANG. ±	PART NAME 品名 DVI24P+5P MALE TO H.D D-SUB 15P FEMALE CHANGER L:42.5mm W:39.5mm SELECTIVE GOLD PLATING BEIGE INSULATOR ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4 REV. 版次 A	PART NO. 料號 C0508-03AASC00R
DATE 制表日 2012/05/30			