



PIN NO.	Dimension			Q'ty/bag
	L1	L	W4	
P2	2.0	5.6	0.3	1000 PCS
P3	4.0	7.6	0.5	1000 PCS
P4	6.0	9.6	1.0	1000 PCS
P5	8.0	11.6	1.0	1000 PCS
P6	10.0	13.6	1.0	1000 PCS
P7	12.0	15.6	1.0	1000 PCS
P8	14.0	17.6	1.0	1000 PCS
P9	16.0	19.6	1.0	1000 PCS
P10	18.0	21.6	1.0	1000 PCS
P11	20.0	23.6	1.0	500 PCS
P12	22.0	25.6	1.0	500 PCS
P13	24.0	27.6	1.0	500 PCS
P14	26.0	29.6	1.0	500 PCS
P15	28.0	31.6	1.0	500 PCS

顏色(Color): 本色(Natural)

材質(Material): 尼龍[PA66 UL94 V-0]

配合端子(Mates with terminal):

T2011-TP900000R

配合塑膠(Mates with housing):

W2111-XXPSTW00R  
W2111-XXPRTW00R

此產品須符合RoHS+無鹵要求  
(The product must conform to the RoHS and Halog - Free directive)

Temperature range	-25°C to +85°C (including temperature rise)
-------------------	--

Electrical performance :

Item	Test Condition	Requirement
1 Contact Resistance	Mate connectors, measure by dry circuit, 20mV MAX., 10mA.	30mΩ MAX
2 Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground.	1000MΩ MIN.
3 Dielectric Strength	Mate connectors, apply 650V AC for 1 minute between adjacent terminal or ground.	No Breakdown and Flashover

RoHS Compliant

**HSM** 玄茂科技股份有限公司  
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 BETTY	TOLERANCE 容許公差 .0 ±0.3 .00 ± ANG. ±	PART NAME 品名 2.0mm HOUSING 1*XXP WHITE COLOR NYLON 66 ROHS
DWG. 製圖 KAREN		
DATE 制表日 2014/06/06	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	REV. 版本 C
PART NO. 料號 H2011-XXPW0000R		