



Dimensional and Order information

Poles	DIM: (mm)	
	A	B
2	6.5	2.5
3	9.0	5.0
4	11.5	7.5
5	14.0	10.0
6	16.5	12.5
7	19.0	15.0
8	21.5	17.5
9	24.0	20.0
10	26.5	22.5
11	29.0	25.0
12	31.5	27.5
13	34.0	30.0
14	36.5	32.5
15	39.0	35.0
16	41.5	37.5

PITCH BETWEEN POLES: 2.5mm
 CURRENT RATING: 3A
 VOLTAGE RATING: 250V
 CONTACT RESISTANCE: INTIAL VALUE/10mΩ max.
 AFTER ENVIRONMENTAL TESTING/20mΩ max.
 INSULATION RESISTANCE: 800 MΩ (min.)
 WITHSTAND VOLTAGE: 1000V AC/MINUTE
 TEMPERATURE RANGE: -25°C TO +85°C
 APPLICABLE WIRE: AWG#22 TO #28
 FEATURES:
 AVAILABLE NUMBER OF CIRCUITS 2 TO 16
 MATERIAL: NYLON 66 UL94V-0

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 2012/6/15	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 零件公差 0 ±0.25 .00 ±0.13 ANG. ± SIZE 紙張尺寸 A4 REV. 版本 B	PART NAME 品名 2.5mm STRAIGHT HOUSING XXP WHITE COLOR ROHS PART NO. 料號 H2503-XXPW0000R