



**NOTES**

Material : Nylon UL94-V0(2).

0.50mm Square Pin.

Pin Material : Brass / Tin-Plated.

Poles	2~20 Poles
Pitch between poles	2.0mm
Rated Voltage	250V AC,DC
Rated current	2A
Withstand Voltage	800V AC/minute
Insulation Resistance	1,000M $\Omega$ /min
Temperaure Range	-25~85°C
Applicable Wire	AWG#24~#30

Circuits	Dimension mm			Circuits	Dimension mm			Circuits	Dimension mm		
	A	B	C		A	B	C		A	B	C
2X2	2.00	6.00	4.90	2X10	18.00	22.00	20.90	2X18	34.00	38.00	36.90
2X3	4.00	8.00	6.90	2X11	20.00	24.00	22.90	2X19	36.00	40.00	38.90
2X4	6.00	10.00	8.90	2X12	22.00	26.00	24.90	2X20	38.00	42.00	40.90
2X5	8.00	12.00	10.90	2X13	24.00	28.00	26.90	~	~	~	~
2X6	10.00	14.00	12.90	2X14	26.00	30.00	28.90	2X30	58.00	62.00	60.90
2X7	12.00	16.00	14.90	2X15	28.00	32.00	30.90				
2X8	14.00	18.00	16.90	2X16	30.00	34.00	32.90				
2X9	16.00	20.00	18.90	2X17	32.00	36.00	34.90				

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.  
核准  
Betty  
DATE 制表日  
2017/07/20

SCALE  
比例 参考  
UNIT  
單位 M M  
PAGE  
張數 1 OF 1

TOLERANCE  
容許公差  
.0 ± 0.30  
.00 ± 0.20  
ANG. ± 3°  
SIZE.  
紙張尺寸 A 4  
REV.  
版次 B

PART NAME 品名  
2.0mm WAFER STRAIGHT TYPE 2XXXP  
TIN PLATED BEIGE COLOR (NYLON 66)  
BAG PACKING ROHS  
PART NO.  
料號 W2113-XXPDSTBCA