



尺寸 (Dimension)		Applicable P.C.B Thickness: 1.6mm		單位 (Unit): mm
P: 2.50 ± 0.05	W: 5.80 ± 0.1	W1: 3.20 ^{+0.07} / _{-0.11}	H2: 12.30 ± 0.2	
L: **** ± 0.25	L1: **** ± 0.25			

L1=CIRCUITS -1 X 2.50		
	L	L1
2	7.5	2.5
3	10.0	5.0
4	12.5	7.5
5	15.0	10.0
6	17.5	12.5
7	20.0	15.0
8	22.5	17.5
9	25.0	20.0
10	27.5	22.5
11	30.0	25.0
12	32.5	27.5
13	35.0	30.0
14	37.5	32.5
15	40.0	35.0

材 質: (MATERIAL): NYLON 66 UL94V0 (GF 25%)
 接觸阻抗: (CONTACT RESISTANCE): 30 mΩ MAX
 絕緣阻抗: (INSULATION RESISTANCE): 1000 MΩ MIN
 耐電壓: (WITHSTANDING VOLTAGE): 1000V AC/MINUTE
 適用溫度: (TEMPERATURE RANGE): -25°C TO +85°C
 電 流: (CURRENT RATING): 3A AC/DC
 電 壓: (VOLTAGE RATING): 250V AC/DC

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	 TOLERANCE 容許公差 .00 ± .ANG. ± SIZE 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 2.5mm WAFER RIGHT ANGLE TYPE WHITE INSULATOR ROHS LOW-LEAD
DWG. 製圖 Yumi		SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1
DATE 制表日 2008/09/03		