



SPECIFICATIONS

Current rating : 2A AC,DC
 Voltage rating : 250V AC,DC
 Temperature range : -25°C to +85 °C
 Contact resistance : 20mΩ Max.
 Insulation resistance : 1000MΩ Min.
 Withstanding voltage : 800V AC/minute
 Material : Nylon 66, UL94V-2

Ordering Information & Dimensions

Poles	Dimension (mm)	
	A	B
2	2.50	5.10
3	5.00	7.60
4	7.50	10.10
5	10.00	12.60
6	12.50	15.10
7	15.00	17.60
8	17.50	20.10
9	20.00	22.60
10	22.50	25.10
11	25.00	27.60
12	27.50	30.10

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2009/6/26	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.3 .00 ± ANG ± SIZE 線規尺寸 A 4 REV 版本 A	PART NAME 品名 DUPOND 2.5mm WAFER ??? RIGHT ANGLE TYPE TIN PLATED WITH LOCKING RIBS IVORY ROHS LOW-LEAD PART NO. 料號 W2660-XXPRX100R