



**MATERIAL & FINISH**

Body: PC. UL94V-2 clean  
 Contact: Copper alloy with gold plated over nickel.

**SPECIFICATION**

Voltage Rating: 125 volts AC, at 1.5 amps.  
 Dielectric Withstanding Voltage: 1000 volts AC.  
 Insulation Resistance: 500 megohms min.  
 Contact Resistance: 30 milliohms max.  
 Durability: 750 cycles.  
 Temp. Rating: -40°C to +85°C

Tol: ±0.15 unless otherwise stated

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 CAT.5e MODULAR PLUG FOR ROUND CABLE 8P8C UL94V-2 GOLD XXU" PLATING ROHS
DWG. 製圖 <b>Hedy</b>	SCALE 比例 參考	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2022/11/18	PAGE 張數 1 / 1	REV. 版次 A	PART NO. 料號 C0020-88RANXX0R