



PCB LAYOUT / TOP VIEW

MATERIAL & FINISH

Housing : PBT. UL94V-0, black

Insert: PBT. UL94V-0, black

Conductor:

- Stamping pin 0.35 × 0.42 mm phosphor bronze,
- Plating: Gold plated over nickel on contact area,
- Tin plated over nickel on solder area.

Temperature: -40°C to 70°C

Durability: 750 cycles min.

ELECTRICAL

Voltage Rating : 125 V

Current Rating : 1.5 A

Contact Resistance : 30 milliohms max.

Insulation Resistance : 500 megohms min.

Dielectric Withstanding Voltage : 1000 V

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 零件公差 0 ± 0.15 .00 ± ANG ±	PART NAME 品名 SIDE ENTRY MINI L/P PCB JACK 6P6C W/ PANEL STOP SPLIT FOOT BLACK COLOR ROHS
DWG. 製圖 <i>Helen</i>	SCALE 比例 參考	UNIT 單位 M M SIZE 紙張尺寸 A 4	PART NO. 料號 C0059-66AAXB00R
DATE 制表日 2015/12/14	PAGE 張數 1 OF 1	REV. 版本 A	