



PCB Layout

ELECTRICAL:

1. Current Rating : 1.5 AMP
2. Voltage Rating : 150 VAC
3. Contact Resistance : 20 Milliohms MAX
4. Insulation Resistance : 500 Milliohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min
6. Durability:750 Cycles.

General tolerance: ±0.2mm General angle tolerance: ±2°

Materials

Housing: Glass Filled Polyester UL94V-0,Black
 Shielding: 0.25mm Thick Alloy,Tin-plated
 Contact:0.45mm Diameter Phosphor Bronze Gold Plating Over Nickel

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 SIDE ENTRY PCB JACK ROUND PIN 10P8C FULLY SHIELDED A TYPE NICKEL SHELL BLACK COLOR ROHS
DWG. 製圖 ABBY		UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2017/04/27	PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 C0060-08AAXB00R