



MATERIAL AND FINSH

Housing: Standard Material Glass Filled Polyester UL 94V-0
 Standard Colour Black.
 Contact: 0.35mm Thickness Phosphor Bronze,
 Shielded: 0.20mm Thickness Copper Alloy With Tin/Nickel
 Plated.
 Gold Plating: Selective Gold Plating.

ELECTRICAL:

- 1. Current Rating : 1.5 AMP
- 2. Voltage Rating : 150 VAC
- 3. Contact Resistance : 20 Milliohms MAX
- 4. Insulation Resistance : 500 Milliohms MIN
- 5. Dielectric Withstanding Voltage : 1000 VAC, 1min

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	SCALE 比例 參考	TOLERANCE 容許公差 0.00 ±0.13 0.0 ±0.25 0 ANG ±0.38 ±3°	PART NAME 品名 SIDE ENTRY P.C.B. JACK 6P6C SMT W/O PANEL STOP(UNSHIELDED) BLACK INSULATOR ROHS
DWG. 製圖 Yumi	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C0065-66DBXB00R
DATE 制表日 2011/03/02	PAGE 張數 1 OF 1	REV. 版次 A	

SUGGESTED PCB LAYOUT (COMPONENT SIDE)