



MATERIAL AND FINISH

Housing: Standard Material Glass Filled Polyester UL 94V-0
Standard Colour Black.

Contact: 0.35mm Thickness Phosphor Bronze,
Shielded: 0.25mm Thickness Copper Alloy With Tin/Nickel
Plated.

Gold Plating: Selective Gold Plating.

Operating Temperature: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$.

ELECTRICAL:

1. Current Rating : 1.5 AMP
2. Voltage Rating : 150 VAC
3. Contact Resistance : 20 Milliohms MAX
4. Insulation Resistance : 500 Milliohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Judie		TOLERANCE 容許公差 .000 ±0.13 ANG±3° .00 ±0.25 0 ±0.38	PART NAME 品名 SIDE ENTRY P.C.B. JACK 6P6C DIP W/ OPANEL STOP (UNSHIELDED) BLACK INSULATOR ROHS
DWG. 製圖 Jolin	SCALE 比例 參考	UNIT 單位 M M	PART NO. 料號 C0065-66PBXB00R
DATE 制表日 2006/12/14	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4 REV. 版次 A	