



MATERIAL AND FINISH

Housing: Standard Material Glass Filled Polyester UL 94V-0
 Standard Color Black.
 Contact: 0.45mm Thickness Phosphor Bronze,
 Shielded: 0.20mm Thickness Copper Alloy With Tin/Nickel
 Plated.
 Gold Plating: Selective Gold Plating.

ELECTRICAL:

1. Current Rating : 1.5 AMP
2. Voltage Rating : 150 VAC
3. Contact Resistance : 20 Milliohms MAX
4. Insulation Resistance : 500 Milliohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

APPD. 核准 Angel DWG. 製圖 Yumi DATE 制表日 2007/08/13		RoHS Compliant HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		PART NAME 品名 SIDE ENTRY PCB DIP JACK 10P8C W/ SHIELDED W/SOLDER PAD W/O SPLIT FOOT FLAT PIN BLACK INSULATOR ROHS	
SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1		TOLERANCE 容許公差 .0 ±0.38 .00 ±0.25 ANG. ±3 SIZE 紙張尺寸 A 4 REV. 版次 A		PART NO. 料號 C0077-08PYXB00R	

SUGGESTED PCB LAYOUT
(COMPONENT SIDE)