



Material:

- Housing: FR52 (UL 94V-0)
- Color: Black
- Spring Wire: Phosphor Bronze
- Plating: Gold Plating Over Nickel In Contact
Tin Plating Over Nickel In Solder Area
- Shield: Brass Plating Nickel Alloy
- operating temperature: 0 ~ 70°C
- Durability: 1000 times
- Soldering Temperature: 245°C for 10 seconds

Electrical:

- Current rating: max 1.5 amp.
- Voltage rating: max 150 volt.
- Insulation Resistance: min 500 megohm/500Vdc
- Contact Resistance: max 40 milliohm/20m Vdc
- Dielectric Voltage: 1000 volts RMS, 60HZ/minute

RoHS Compliant

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. BETTY		TOLERANCE .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	PART NAME 品名 SIDE ENTRY PCB SMT JACK 6P6C W/SHIELDED W/SOLDER PAD W/O SPLIT FOOT FLAT PIN SELECTIVE GOLD 6U" PLATING PBT MATERIAL BLACK INSULATOR ROHS
DWG. KAREN	SCALE 参考	UNIT M M	PART NO. 料號 C0077-66DYQB00R
DATE 2014/12/03	PAGE 1 OF 1	SIZE. A 4 REV. A	