



IC SOCKET	A±0.20	B±0.10
24P	30.48	27.94
28P	35.56	33.02
32P	40.64	38.10
40P	50.80	48.26
42P	53.34	50.80
48P	60.96	58.42

**BODY**  
 MATERIAL: PBT+GLASS(UL94V-0)  
 COLOR: BLACK

**TERMINAL**  
 MATERIAL: PHOS. BRONZE  
 PLATE: TIN PLATED 100U" MIN.

CURRENT: 1 AMP  
 WITHSTANDING VOLTAGE: AC 1000V 5S  
 INSULATION RESISTANCE: 1000MΩ 500V DC  
 WORKING PRESSURE: -55°C ~ +105°C

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 0 ±0.20 .00 ±0.10 ANG±	PART NAME 品名 I.C. SOCKET 2.54mm XXP 0.6'(=15.24mm) WITHOUT BAR TIN PLATING BLACK INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C0102-XXCNTB00R
DATE 制表日 2013/08/07	PAGE 張數 1 OF 1	REV. 版次 A	