



BAR	No of contacts	Dim A	Dim B
no bar	6	5.08	7.62
no bar	8	7.62	10.16
no bar	10	10.16	12.70
no bar	12	12.70	15.24
no bar	14	15.24	17.78
no bar	16	17.78	20.32
with bar	18	20.32	22.86
with bar	20	22.86	25.40
with bar	22	25.40	27.94
with bar	24	27.94	30.48
with bar	28	33.02	35.56
with bar/2	32	38.10	40.64

Technical Data:

Material:

Insulator body(housing):PBT(black UL-94V0)
 Pin(outer sleeve):Brass,machined,CuZn38pb2
 Tin plated:2um/80u"nickel,5um/200u"Tin plated
 Clip(4 finger):Beryllium copper
 Gold plated:2um/80u"nickel/0.025um/1u" full Gold
 Electrical

Current rating: 3 Amps /contact max
 Insulation resistance: > 1000 MΩ at V=100 V
 Operating: 60 Veff

Mechanical

Operating temperature:Gold plated: -55°C to +125°C
 Tin plated : -40°C to +105°C
 Soldering temperature: + 200° C 10s max

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 2.54mm IC SOCKET MACHINED PIN 4 FINGERED CLIP ROW PITCH:0.3" XXP PIN:TIN CLIP:GOLD PLATING WIRE WRAP PIN ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C0110-XXSACB00R
DATE 制表日 2012/07/28	PAGE 張數 1 OF 1	REV. 版次 A	