



PCB Layout Diagram
Top View

NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
3	TERMINAL(-)	1	PHOSPHOR BRONZE, T=0.15mm	Sn-Plating
2	TERMINAL(+)	1	PHOSPHOR BRONZE, T=0.15mm	Sn-Plating
1	HOUSING	1	LCP	WHITE

NOTE:

1.MATERIAL:

a.HOUSING:LCP UL94V-0

b.CONTACT:PHOSPHOR BRONZE

(SURFACE PLATING: Sn100U"-120U")

SEE ORDERING INFORMATION

2.ELECTRIC:

a.CONTACT RESISTANCE: 30 MILLIOHMS MAX

b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN

c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL

d.OPERATING TEMPERATURE: -25°C~ +85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		UNLESS OTHERWISE SPECIFIED TOLERANCES	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	BATTERY HOLDERS FOR CR1632 SMT TYPE
DATE 制表日	2019/01/07	UNIT 單位 M M	TIN PLATING BEIGE COLOR MATERIAL:LCP
		PAGE 張數 1 OF 1	TRAY PACKING ROHS
		REV. 版次 A	PART NO.
			料號 C0177-02DNTCH0R