



MATERIALS:

PLASTIC HOUSING: ENGINEERING THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.
 CONTACTS: PHOSPHOR BRONZE
 PLATING: GOLD PLATING OVER NICKEL IN CONTACT.
 TIN PLATING OVER NICKEL IN SOLDER AREA.
 SHIELDED: BRASS WITH NICKEL PLATED

PCB LAYOUT/TOP VIEW

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RNS.
2. COURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 40 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN
500 VDC
5. DIELECTRIC STRENGTH : 1500 VAC to 60S
6. STORAGE LIFE : -40 °C TO +85 °C
7. OPERATING : -40 °C TO +85 °C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	PART NAME 品名 TOP ENTRY PCB JACK 8P8C PRESS FIT TYPE WITHOUT PANEL STOP FULLY SHIELDED D TYPE (BEHIND PEG 3.81mm) FLAT PIN SELECTIVE GOLD 6U" PLATING BLACK COLOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C0230-88DEQB00R
DATE 制表日 2023/10/26	PAGE 張數 1 OF 1	REV. 版次 C	