



**1.MATERIALS :**

- a. BODY : ZINC ALLOY,DIE CASTIN NICKEL PLATED.
- b. CONTACT: BRASS NICKEL PLATED.
- c. BRACKET: A.B.S .
- d. INSULATOR: ENGINEER PLASTIC POM .

**2.NOMIAL IMPEDENCE 50 OHMS.**

**3.FREOUENCY RANGE: 0-2 GHZ.**

**4.MAX PEAK VOLTAGE: 500V**

**5.DIELECTRIC STRENGTH WITHSTAND 1.5KV NNS.**

**6.INSULATION RESISTANCE AT 500 VDE 5000 MEGOHMS MAL.**

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-3 +0.02 3-5 +0.04 5-30 +0.06 30-100 +0.1 100-315 +0.16 315-1000 +0.2 1000-2000 +0.4	PART NAME 品名 BNC PCB 2X1 PORT JACK RIGHT ANGLE TYPE 50ohm WITHOUT FILTER ZINC ALLOY/NICKEL PLATED ROHS
DWG. 製圖 Betty	UNIT 單位 M M		SIZE. 紙張尺寸 A 4
DATE 制表日 2024/04/10	PAGE 張數 1 OF 1	REV. 版次 A	

PCB