



PCB LAYOUT

1. Mating: 1/4-36 UNS Thread coupling
2. Durability: 500 cycles
3. Temperature range: -55°C~+155°C
4. Impedance: 50ohm
5. Frequency: 0~6GHz max
6. VSWR: 1.60 max
7. Working voltage: 335 Volts rms
8. Dielectric withstanding voltage: 500 Volts rms
9. Insulation resistance :5000 MΩ min
10. Contact resistance: center conductor 3.0mΩ

3	INSULATOR	PTFE WHITE	1
2	PIN	BRASS GOLD-PLATING	1
1	BODY	BRASS SOCKET	1
No.	Description	Material	Q'ty

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 2016/8/30	SCALE 比例 <i>Helen</i> UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3° SIZE. 紙張尺寸 A 4 REV. 版本 A	PART NAME 品名 RF CONNECTOR-SMA JACK 90° 50ohms BODY:BRASS/NICKEL PLATED PIN:GOLD FLASH PLATED ROHS PART NO. 料號 C0412-RJRANG00R