



ELECTRICAL SPECIFICATIONS:
 IMPEDANCE: 50 OHM
 WITHSTANDING VOLTAGE: 500VRMS
 INSULATION RESISTANCE: 5,000 MEGOHMS MIN
 CONTACT RESISTANCE:
 CENTER CONTACT 3.0 MILLIOHMS MAXIMUM,
 OUTER CONTACT 2.0 MILLIOHMS MAXIMUM.

DIMENSIONS ARE IN MILLIMETERS				
UNLESS OTHERWISE SPECIFIED TOLERANCES				
				0.5-5 =±0.2
				6-30 =±0.4
				30-120 =±0.6
				120-315 =±1
				315-1000 =±1.6
				1000-2000 =±2.4
NO	DESCRIPTION	MATERIAL	FINISH	QTY

RoHS Compliant

APPD. 核准
 DWG. 製圖
 Betty
 DATE 制表日
 2015/06/11

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 / 1

TOLERANCE 容許公差
 .0 ±
 .00 ±
 ANG. ±

SIZE. 紙張尺寸 A4
 REV. 版次 B

PART NAME 品名
 BNC FEMALE P.C MOUNT RIGHT ANGLE TYPE 50Ω
 L:22.0mm METAL BODY ZINC ALLOY
 / NICKEL PLATED ROHS

PART NO. 料號
C0462-RABM0000R

1 2 3 4 5 6 7 8