



ELECTRICAL SPECIFICATIONS:  
 IMPEDANCE:50 OHM  
 WITHS TANDING VOLTAGE:500VRMS  
 INSULATION RESISTANCE:5000 MEGOHMS MIN  
 CONTACT RESISTANCE:  
 CENTER CONTACT 3.0 MILLIDHMS MAXIMUM  
 OUTER CONTACT 2.0 MILLIONHMS MAXIMUM

DIMENSIONS ARE IN MILLIMETERS	
UNLESS OTHERWISE SPECIFIED TOLERANCES	
0.5-5	=±0.2
6-30	=±0.4
30-120	=±0.6
120-315	=±1
315-1000	=±1.6
1000-2000	=±2.4

NO	DESCRIPTION	MATERIAL	FINISH	QTY
4	PIN	BRASS	GOLD	1
3	INSULATOR	POM	WHITE	2
2	BODY	ZINC	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1

PCB HOLE CONFIGURATION  
 RECOMMENDED PANEL CUTOUTS

<b>RoHS</b> <b>Compliant</b>	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
	APPD. 核准 DWG. 製圖 Hedy	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1
DATE 制表日 2018/02/27		PART NAME 品名 BNC FEMALE P.C.B MOUNT RIGHT ANGLE TYPE L:27.3mm METAL BODY ZINC ALLOY / NICKEL PLATED ROHS PART NO. 料號 C0462-RXCM0000R