



● MATERIALS: (RoHS Compliant)

Housing: Plastic Thermoplastic  
P.B.T UL94V-0 Black  
Contacts: Phosphor Bronze Gold  
Selective Plated

Front Shell: Steel Nickel Plated Over Copper

● ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 0.5 Amp  
Dielectric Withstanding Voltage: 500V AC  
Insulation Resistance: >500MΩ/Min  
Contact Resistance: 35mΩ/Max  
Operation Temperature: -55°C ~ +85°C

● MATERIALS: (RoHS Compliant)

Back Shell: Zinc Alloy Nickel Plated Over Copper  
Flat Screws: Steel Nickel Plated Over Copper  
Cable Clipper: Steel Nickel Plated Over Copper  
Spring Latches: Stainless Steel

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖		0 ± 0.3 ANG ±	
DATE 制表日	SCALE 比例	SIZE. 紙張尺寸	PART NO.
2014/3/20	1 OF 1	REV. 版本	

UNIT 單位	MM
PAGE 張數	1 OF 1

REV. 版本	A
料號	C0509-26MBLEZOR