

● **MATERIALS:**


Housing And Cover : Plastic Thermoplastic
P.B.T UL94V-0 Black
Contacts : Phosphor Bronze Gold
Selective Plated
Bracket : Zinc Alloy Nickel
Plated Over Copper

● **ELECTRICAL CHARACTERISTICS:**

Contact Current Rating: 0.5 Amp
Dielectric Withstanding Voltage: 500V AC
Insulation Resistance: >500MΩ/Min
Contact Resistance: 35mΩ/Max
Operation Temperature: -55°C ~ +85°C

C **0516** — **68** **F** **B** **N** **B** **X** **B** **R**

- | | | | |
|-------------------------------|---|---|--|
| 1. PRODUCTS:
C: Connector | 5. SHELL OPTION:
B: Metal Shell W/O
Front Latch | 7. MOUNTING OPTION:
A: Thread Insert
2-56 UNC
B: Thread Insert
4-40 UNC | 8. CONTACT PLATING:
S: Selective Gold
E: Selective Gold
5U* |
| 2. SERIES NO.:
0516 | 6. ACCESSORIES:
N: W/O S/R | | 9. OTHERS:
B: Black Insulator |
| 3. CONTACT NO.:
68 | | | 10. R: ROHS |
| 4. CONTACT TYPE:
F: Female | | | |



View A

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 SCSI-III D-SUB IDC 1.27mm 68P FEMALE WITHOUT S/R WITHOUT FRONT LATCH METAL SHELL BLACK COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0516-68FBNXXBR
DATE 制表日 2013/08/20	PAGE 張數 1 OF 1	REV. 版次 A	