



Recommended PCB Layout

1. Material: $\triangle E$
 Insulator: LCP, UL94V-0 $\triangle F$
 Contact: Copper Alloy
 Shell: SPCC
 Harpoon: Copper Alloy
 Rivet: Copper Alloy
 Screw: Brass

2. Specification:
 Contact Current Rating: 1 Amperes.
 Dielectric Withstanding Voltage: AC 500V at sea level.
 Insulation Resistance: 1000 Megohms Min.
 Contact Resistance: 30 Milliohms Max.
 Operation Temperature: -55°C to +105°C.

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	GENERAL TOLERANCE: X ±0.30 Ang. ±3' XX ±0.20 XXX ±0.05	PART NAME 品名 D-SUB PCB R/A FOR NOTEBOOK SMT TYPE 9P FEMALE THREAD INSERT 4-40UNC W/BOARDLOCK W/O SCREWS (POST SPACING=15.9mm) NICKEL SHELL BLACK COLOR MATERIAL:LCP ROHS PART NO. 料號 C0527-09FBANXBN
DWG. 製圖 Betty		DATE 制表日 2017/04/27	

DATE 制表日 2017/04/27	REV. 版次 C
------------------------	--------------

REV. 版次 C
