



ELECTRICAL DATA:

Rated Voltage: 350V AC
 Rated Current: 5A
 Withstand Voltage: 500V AC(RMS)
 Insulation Resistance: Over 1000MΩ
 Contact Resistance: 30 mΩ Max.
 Temperature : -40°C to +100°C.

Material:

Insulator: PBT+30% Glass Fiber UL94V-0
 Pin contacts: Brass or Phosphor Bronze
 Gold Plated & Tin Plated
 Shell: Steel, SPCC Nickel or Tin Plated

ORDER INFORMATION

C 0 5 4 0 -

X	X	F	A	A	X	X	X	R
1	2	3	4	5	6	7	8	

- | | |
|---|---|
| 1. CONTACT NO:
09, 15, 25, 37, 50 | 6. CONTACT PLATING
S: SELECTIVE GOLD
G: GOLD FLASH
A: GOLD 5U"
B: GOLD 10U"
C: GOLD 15U"
D: GOLD 30U" |
| 2. CONTACT TYPE:
F: FEMALE | 7. OTHERS:
W: WHITE
L: BLUE
B: BLACK
G: GREY |
| 3. MOUNTING OPTION:
A: THROUGH HOLE | 8. ROHS LOW-LEAD |
| 4. ACCESSORIES:
A: NON ACCESSORIES | |
| 5. SHELL PLATING:
T: TIN
N: NICKEL
Z: ZINC(CHROMATIC)
A: TIN+DIMPLE
B: NICKEL+DIMPLE | |

M/F \ DIM	A	B	C	D	E	F	G
09	16.30	25.00	30.80	19.30	7.90	12.50	10.70
15	24.70	33.30	39.10	27.50	7.90	12.50	10.70
25	38.40	47.00	53.00	41.30	7.90	12.50	10.70
37	54.80	63.50	69.30	57.70	7.90	12.50	10.70
50	52.40	61.10	66.90	55.30	10.80	15.40	13.60



HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. HELEN	 SCALE 参考	TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10	PART NAME 品名
DWG. ABBY		UNIT M M	D-SUB SOLDER TYPE STAMPED PIN FEMALE THROUGH HOLE SHELL ROHS
DATE 2014/04/01	PAGE 1 OF 1	SIZE. A 4 REV. B	PART NO. 料 號 C0540-XXFAAXXR