



- 一、 MATERIAL:
1. Insulator: PBT+30%Glass Fiber (UL94V-0)
 2. Contact: Brass
 3. Contact Plated: Glod Flash over Tin
 4. Shell: Stell, Nickel Plated
- 二、 SPECIFICATION:
1. Current Rating: 5 AMPS
 2. Insulation Resistance: 1000M Ω MIN. At 500VDC
 3. Dielectric Strength: 500V for One minute
 4. Operation Temperatur: -55℃~+105℃.

PINS \ DIM	A±0.20	B±0.20	C±0.20	D±0.20
9P	30.80	25.00	16.90	19.20
15P	39.20	33.33	25.30	27.50
25P	52.00	47.00	39.00	41.30
37P	69.40	63.50	55.40	57.70

C **0540** — **09** **M** **A** **A** **B** **S** **B** **R**

- | | | | |
|--|--|---|---|
| 1. PRODUCTS:
C: Connector | B: Hex Screw+1.5mm Nut
C: 3.8mm Open Hex Rivet
D: 5.8mm Open Hex Rivet
E: 5.8mm*M3
F: 5.8mm Close Hex Rivet
H: 4.0mm*M3
I: 6.0mm Boardlock Rivet | Loose Screws
D: Front Rivet+ Fix Screws
E: Rear Rivet
F: Rear Rivet+ Loose Screws
G: Rear Rivet+ Fix Screws | 8. CONTACT PLATING:
S: Selective Gold
G: Gold Flash |
| 2. SERIES NO.:
0540 | 6. ACCESSORIES:
A: Non Accessories
B: Front Rivet
C: Front Rivet+ | 7. SHELL PLATING:
A: Tin+Dimple
B: Nickel+Dimple | 9. OTHERS:
W: White Insulator
L: Blue Insulator
B: Black Insulator
G: Grey Insulator
10. R: ROHS |
| 3. CONTACT NO.:
09, 15, 25, 37, 50 | | | |
| 4. CONTACT TYPE:
M: Male | | | |
| 5. MOUNTING OPTION:
A: Through Hole | | | |

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 0.25 0°±2.0° 0.03±0.15 0.00±1.0° 0.00±0.05 0.00±0.5°	PART NAME 品名 D-SUB SOLDER TYPE STAMPED PIN XXP MALE THROUGH HOLE NICKEL SHELL+DIMPLE ROHS
DWG. 製圖 KAREN	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C0540-XXMAABSXR
DATE 制表日 2015/04/09	PAGE 張數 1 OF 1	REV. 版次 B	