



P. C. BOARD LAYOUT

**MATERIAL:**

Insulator: PBT+30% Glass Fiber(UL94V-0)  
 Contacts: Phosphor Bronze or Brass(Standard it Brass)  
 Contact Plated: Gold over Nickel  
 Shell: Steel, Nickel plated or Tin plated

**SPECIFICATION:**

Current Rating: 5Amps  
 Insulation Resistance: 1000MΩ Min. at 500V DC  
 Withstanding Voltage: 500V AC/minute  
 Operating Temperature: -40°C ~ +105°C

M/F	DIM	A	B	C	D	E	F	G
09		16.30	25.00	30.80	19.30	7.90	12.50	10.70
15		24.70	33.30	39.10	27.50	7.90	12.50	10.70
25		38.40	47.00	53.00	41.30	7.90	12.50	10.70
37		54.80	63.50	69.30	57.70	7.90	12.50	10.70

**RoHS Compliant**

**HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.		TOLERANCE	PART NAME 品名
DWG. Helen	SCALE 参考	.0 ± 0.25 .00 ± ANG. ±	D-SUB PCB STRAIGHT STAMPED PIN XXP FEMALE ROHS
DATE 2015/2/6	UNIT M M	SIZE. A 4	PART NO. C0541-XXFAAXXR
	PAGE 1 OF 1	REV. B	料號