


**MATERIAL:**  
 Insulator: PBT+30% Glass Fiber  
 UL94V-0  
 Pin contacts: Brass or Phosphor Bronze  
 Gold Plated & Tin plated  
 Shell: Steel, SPCC  
 Nickel & Tin Plated

**ELECTRICAL DATA:**  
 Rated Voltage: 350V AC  
 Rated Current: 5A  
 Withstand Voltage: 500V AC(RMS)  
 Insulation Resistance: Over 1000MΩ  
 Contact Resistance: 5MΩ AT 1A  
 Temperature: -40°C ~ +100°C

M/F	DIM	A	B	C	D	E	F	G
09		16.90	25.00	30.80	19.30	8.30	12.50	10.70
15		25.30	33.30	39.10	27.50	8.30	12.50	10.70
25		39.00	47.00	53.00	41.30	8.30	12.50	10.70
37		55.40	63.50	69.30	57.70	8.30	12.50	10.70

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>HELEN</b>	 TOLERANCE 容許公差 .0 ± .00 ± ANG ±	<b>PART NAME 品名</b> D-SUB PCB STRAIGHT STAMPED PIN XXP MALE 5.8mm OPEN HEX RIVET REAR RIVET FIX SCREWS NICKEL SHELL+DIMPLE BLACK INSULATOR ROHS	
DWG. 製圖 <b>ABBY</b>	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4 REV. 版次 A	<b>PART NO. 料號</b> <b>C0541-XXMDGXXXR</b>
DATE 制表日 <b>2018/08/17</b>			