



NO. OF Contact	A±0.25	B±0.23	C±0.38
09M	16.92	24.99	30.61
15M	25.25	33.32	39.14
25M	38.4	47.04	53.04
37M	55.42	62.5	69.32

Contact Resistance: 30mΩ max. at DC 100mA
 Insulator Resistance: 1000mΩ min. at DC 500V
 Current Rating: 1AMP

Dielectric Withstanding
 Voltage: AC 1000V For 1 minut
 Operating Temperature: -55°C~+105°C
 Contact: Brass
 Housing: PBT & 30% Glass Fiber(UL 94V-0)

13.84M

ROHS

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 D-SUB PCB RIGHT ANGLE 13.84mm STAMPED PIN XXP MALE RIVET W/BOARDLOCK W/O SCREWS TIN SHELL +DIMPLE GOLD PLATING BLACK ROHS LOW-LEAD
DWG. 製圖 Yumi	SCALE 比例 參考	UNIT 單位 M M	PART NO. 料號 C0552-XXMBAAGBR
DATE 製表日 2008/09/18	PAGE 張數 1 OF 1	REV. 版次 B	