



MATERIAL :
Contacts:Brass.
Insulator:PBT&30% Glass Fiber (UL 94V-0)
SHELL: Nickel
 Top connector:9-pos. Black
 Bottom Connector:9-pos. Black
 Contact Resistance:30mΩ max. at DC 100mA
 Insulator Resistance:1000mΩ min. at DC 500V
 Current Rating:5AMP
 Voltage:AC 1000V For 1 minute
 Operating Temperature:-55°C~+105°C

P. C. B LATOUT

APPD. 核准 HELEN			TOLERANCE 容許公差 .0 ± 0.25 .00 ± ANG. ±	PART NAME 品名 D-SUB RIGHT ANGLE DUAL PORT DB9M/DB9F L-SHAPE (CENTER LINE 6.9mm) FIX SCREWS (4.8x11.8mm)PORT SPACING 15.875mm GOLD FLASH PLATING BLACK INSULATOR ROHS
DWG. 製圖 ABBY				
DATE 制表日 2012/10/18		UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0553-09BBCAGBR
		PAGE 張數 1 OF 1	REV. 版次 A	

RoHS Compliant
玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.