



PLATING:
 GOLD FLASH
 GOLD 15U"
 GOLD 30U"

MATERIAL:
 Insulator: PBT+30% Glass Fiber
 UL94V-0
 Pin contacts: Brass or Phosphor Bronze
 Gold Plated & Tin plated
 Shell: Steel,SPCC
 Nickei & Tin Plated

ELECTRICAL DATA:
 Rated Voltage: 350V AC
 Rated Current: 5A
 Withstand Voltage: 500V AC(RMS)
 Insulation Resistance: Over 1000 MΩ
 Contact Resistance: 5 MΩ AT 1A (Gold Flash)
 Temperature: -40°C~100°C

| DIM M/F | A | B | C | D | E | F | G | H | I | J |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 15 | 16.30 | 25.00 | 30.80 | 7.90 | 12.50 | 7.039 | 2.286 | 1.981 | 10.70 | 19.30 |
| 26 | 24.70 | 33.30 | 39.10 | 7.90 | 12.50 | 6.871 | 2.286 | 1.981 | 10.70 | 27.50 |
| 44 | 38.40 | 47.00 | 53.00 | 7.90 | 12.50 | 6.863 | 2.286 | 1.981 | 10.70 | 41.30 |
| 62 | 54.80 | 63.50 | 69.30 | 7.90 | 12.50 | 6.998 | 2.413 | 1.981 | 10.70 | 57.70 |
| 78 | 52.40 | 61.10 | 66.90 | 10.70 | 15.40 | 7.627 | 2.413 | 2.083 | 13.80 | 55.30 |

| | | | |
|------------------------|-------------------|--|---|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 Hedy | SCALE 比例 参考 | TOLERANCE 容許公差 .0 ± .00 ± ANG. ± | PART NAME 品名 H.D. D-SUB SOLDER TYPE STAMPED PIN XXP FEMALE THROUGH HOLE TIN SHELL BLACKROHS LOW-LEAD |
| DWG. 製圖 Yumi | UNIT 單位 MM | SIZE 紙張尺寸 A 4 | PART NO. 料號 C0560-XXFAATXBR |
| DATE 制表日 2009/08/13 | PAGE 張數 1 OF 1 | REV. 版次 A | |