



**P.C BOARD LAYOUT**

**MATERIAL:**  
**Insulator:** PBT+30% Glass Fiber  
 UL94V-0  
**Pin contacts:** Brass or Phosphor Bronze  
 Gold Plated & Tin plated  
**Shell:** Steel,SPCC  
 Nickel & Tin Plated

**ELECTRICAL DATA:**  
**Rtaed Voltage:** 350V AC  
**Rated Current:** 5A  
**Withstand Voltage:** 500V AC(RMS)  
**Insulation Resistance:** Over 1000 MΩ  
**Contact Resistance:** 5 MΩ AT 1A  
**Temperature:** -40℃~100℃

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN		<b>TOLERANCE 容許公差</b> 0. ± 10 .0 ± 0.10 .00 ± 0.05	<b>PART NAME 品名</b> H.D. D-SUB PCB STRAIGHT STAMPED PIN 15P FEMALE REAR RIVET 6mm BOARDLOCK LOOSE SCREWS ROHS
DWG. 製圖 ABBY	<b>SCALE 比例 參考</b> UNIT 單位 M M	<b>SIZE 板張尺寸</b> A 4	<b>PART NO. 料號</b> C0561-15FIFXXXR
DATE 制表日 2016/03/04	<b>PAGE 張數</b> 1 OF 1	<b>REV. 版本</b> A	