



6. ACCORIES: (OPTION)
A: Non Accessories
B: Add Screws (4.8*11.8)
C: Fix Screws (4.8*11.8)

MATERIAL:
 1.Insulator:PBT+30%Glass Fiber (UL94V-0)
 2.Contact:Brass
 3.Contact Plated:Glod Flash over Tin Or Glod Plated Or Tin Plated
 4.Shell:Stell,Nickel Plated

SPECIFICATION?
 1.Current Rating:5 AMPS
 2.Insulation Resistance: 1000MΩ MIN. At 500VDC
 3.Dielectric Strength: 500V for One minute
 4.Operation Temperature: -55° C~+105° C.

PIN	A	B	C
15	30.80	24.99	16.90
26	39.20	33.30	25.25
44	53.10	47.04	38.96
62	69.34	63.50	55.42

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考	TOLERANCE .0±0.30 .07±1.0' .00±0.25 .00'±0.5' .000±0.05 .000'±0.1'	PART NAME 品名 HIGH DENSITY D-SUB PCB RIGHT ANGLE TYPE STAMPED PIN XXP MALE WITH BOARDLOCK NICKEL SHELL+DIMPLE BLACK INSULATOR
DWG. 製圖 BETTY	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C0562-XXMAC(A,B,C)XBR
DATE 制表日 2009/09/23	PAGE 張數 1 OF 1	REV. 版次 A	