



AWG 26-30

- NOTES:
- MATERIAL: C5191
THICKNESS=0.20mm
 - PLATING: Δ NICKEL ALL OVER. THICKNESS AT 30u INCH
 Δ GOLD FLASH OVER NICKEL. THICKNESS AT 3u~5u INCH
 - QUANTITY: 10,000PCS/REEL
 - GENERAL TOLERANCE ± 0.15 mm ; ANGLE TOLERANCE $\pm 1.0^\circ$

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 2010/03/25	Hedy	TOLERANCE 容許公差 X ±0.05 XX ±0.02 XXX ±0.002	PART NAME 品名 HIGH DENSITY D-SUB CRIMPING FEMALE TERMINAL PHOSPHOR BRONZE MATERIAL SELECTIVE GOLD 26~30AWG 1ROLL=10000PCS LOW-LEAD
SCALE 比例 UNIT 單位 MM	REFERENCE 參考 PAGE 張數 1 / 1	SIZE 紙張尺寸 A 4 REV. 版本 A	PART NO. 料號 C0563-TFSPK000R