



"D-SUB" CONNECTOR STRAIGHT DIP
 TYPE "SOCKET" MACHINED PIN
 PRODUCT: ROHS
 MATERIAL & FINISH
 SHELL:
 STEEL
 OR TIN PLATED
 PIN CONTACT:
 BRASS
 GOLD PLATED OVER NICKEL
 INSULATOR:
 PBT & GLASS-FIBRE REINFORCED
 UL-94-V0
 NUMBER OF CONTACT:
 9, 15, 25, 37, 50
 CURRENT RATING:
 5 AMP
 DIELECTRIC STRENGTH:
 1000V FOR ONE MINUTE
 INSULATOR RESISTANCE:
 1000M Ω MIN. AT 500V DC
 TEMPERATURE:
 -55°C - +105°C

PIN	A	B	C	D	E	F	G
9P	0.643 16.33	0.984 24.99	1.213 30.81	0.759 19.28	0.0394 1.000	0.425 10.80	0.170 4.32
15P	0.971 24.66	1.312 33.32	1.541 39.14	1.083 27.51	0.0394 1.000	0.425 10.80	0.170 4.32
25P	1.511 38.38	1.852 47.04	2.088 53.04	1.625 41.30	0.0394 1.000	0.425 10.80	0.170 4.32
37P	2.159 54.84	2.500 63.50	2.729 69.32	2.272 57.71	0.0394 1.000	0.425 10.80	0.170 4.32
50P	2.060 52.34	2.406 61.11	2.634 66.92	2.177 55.30	0.0394 1.000	0.425 10.80	0.170 4.32

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE X ±0.30 XX ±0.25 XXX ±0.15 ANG. ±2°	PART NAME 品名 D-SUB PCB STRAIGHT MACHINED PIN XXP FEMALE TIN SHELL GOLD PLATING ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C0571-XXFAATGXR
DATE 製表日 2016/05/05	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	REV. 版次 A