



MATERIAL & FINISH
 SHELL :
 TIN PLATED
 PIN CONTACT :
 GOLD PLATED OVER NICKEL
 INSULATOR :
 PBT & GLASS-FIBRE REINFORCED
 CURRENT RATING :
 5 amp.
 DIELECTRIC STRENGTH :
 1000V FOR ONE MINUTE
 INSULATOR RESISTANCE :
 1000MΩMIN. At 500V DC
 TEMPERATURE :
 -55°C ~ +105°C

SHELL SIZE	A	B	C	D	E
	0.010 0.25	0.005 0.13	0.015 0.38	0.010 0.25	0.015 0.38
9	0.643 16.33	0.984 24.99	1.213 30.81	0.759 19.28	0.429 10.90
15	0.971 24.66	1.312 33.32	1.541 39.14	1.083 27.55	0.429 10.90
25	1.511 38.38	1.852 47.04	2.088 53.04	1.625 41.28	0.429 10.90
37	2.159 54.84	2.500 63.50	2.729 69.32	2.272 57.71	0.429 10.90
50	2.060 52.43	2.406 61.10	2.635 66.93	2.178 55.32	0.429 10.90

SERIES	DIM-7.2
FOOT-PRINT	0.283 7.19

RoHS Compliant

HSM 玄茂科技股份有限公司
Hsuan Mao Technology Co., LTD.

APPD.		TOLERANCE	PART NAME 品名
DWG.	SCALE 参考	.00 ±0.35 .000 ±± ANG. ±±	D-SUB PCB RIGHT ANGLE 7.2mm MACHINED PIN XFP FEMALE W/O BRACKET NON ACCESSORIES GOLD FLASH PLATING ROHS
DATE	UNIT mm	SIZE A 4	PART NO.
2014/04/07	PAGE 1 OF 1	REV. A	料號 C0572-XXFAAXGXR