

	1	2	3	4	5	6	7	8																																																										
A	<p>MATERIAL AND FINISH :</p> <p>SHELL : STEEL TIN PLATED</p> <p>PIN CONFACTS : BRASS GOLD PLATED OVER NICKEL</p> <p>INSULATOR : PBT GLASS FIBER REINFORCED</p> <p>CURRENT RATING : 5A</p> <p>DIELECTRIC STRENGTH : 1000V FOR ONE MINUTE</p> <p>INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC</p> <p>TEMPERATURE : -55° C~105° C</p> <p>CONTACT RESISTANCE : < 20 MILLIOHM (Gold Flash)</p>																																																																	
B																																																																		
C																																																																		
D																																																																		
E	<p>PLATING:</p> <p>GOLD FLASH</p> <p>GOLD 15U"</p> <p>GOLD 30U"</p>																																																																	
F																																																																		
G	<table border="1"> <thead> <tr> <th>PIN</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> </tr> </thead> <tbody> <tr> <td>15P</td> <td>30.8</td> <td>16.9</td> <td>2.29</td> <td>24.99</td> <td>19.2</td> </tr> <tr> <td>26P</td> <td>39.1</td> <td>25.5</td> <td>2.29</td> <td>33.32</td> <td>27.7</td> </tr> <tr> <td>44P</td> <td>53.0</td> <td>39.0</td> <td>2.29</td> <td>47.04</td> <td>41.1</td> </tr> <tr> <td>62P</td> <td>69.3</td> <td>55.4</td> <td>2.41</td> <td>63.5</td> <td>57.3</td> </tr> <tr> <td>78P</td> <td>66.9</td> <td>52.86</td> <td>2.41</td> <td>61.11</td> <td>55.3</td> </tr> </tbody> </table>				PIN	A	B	C	D	E	15P	30.8	16.9	2.29	24.99	19.2	26P	39.1	25.5	2.29	33.32	27.7	44P	53.0	39.0	2.29	47.04	41.1	62P	69.3	55.4	2.41	63.5	57.3	78P	66.9	52.86	2.41	61.11	55.3	<div style="display: flex; justify-content: space-between;"> <div style="border: 1px solid black; padding: 5px;"> <p>RoHS Compliant</p> </div> <div style="text-align: center;"> <p>HSM 玄茂科技股份有限公司</p> <p>HSUAN MAO TECHNOLOGY CO., LTD.</p> </div> </div> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">APPD. 核准</td> <td style="width: 15%;">Hedy</td> <td style="width: 15%;">TOLERANCE 容許公差</td> <td style="width: 15%;">PART NAME 品名</td> </tr> <tr> <td>DWG. 製圖</td> <td>Yumi</td> <td>SCALE 比例 參考</td> <td>HIGH DENSITY D-SUB SOLDER TYPE MACHINED PIN XXP MALE THROUGH HOLE TIN SHELL+DIMPLE ROHS</td> </tr> <tr> <td>DATE 制表日</td> <td>2009/08/13</td> <td>UNIT 單位 M M</td> <td>PART NO.</td> </tr> <tr> <td></td> <td></td> <td>PAGE 張數 1 OF 1</td> <td>料號 C0574-XXMAAAXXR</td> </tr> <tr> <td></td> <td></td> <td>REV. 版次 A</td> <td></td> </tr> </table>				APPD. 核准	Hedy	TOLERANCE 容許公差	PART NAME 品名	DWG. 製圖	Yumi	SCALE 比例 參考	HIGH DENSITY D-SUB SOLDER TYPE MACHINED PIN XXP MALE THROUGH HOLE TIN SHELL+DIMPLE ROHS	DATE 制表日	2009/08/13	UNIT 單位 M M	PART NO.			PAGE 張數 1 OF 1	料號 C0574-XXMAAAXXR			REV. 版次 A			
PIN	A	B	C	D	E																																																													
15P	30.8	16.9	2.29	24.99	19.2																																																													
26P	39.1	25.5	2.29	33.32	27.7																																																													
44P	53.0	39.0	2.29	47.04	41.1																																																													
62P	69.3	55.4	2.41	63.5	57.3																																																													
78P	66.9	52.86	2.41	61.11	55.3																																																													
APPD. 核准	Hedy	TOLERANCE 容許公差	PART NAME 品名																																																															
DWG. 製圖	Yumi	SCALE 比例 參考	HIGH DENSITY D-SUB SOLDER TYPE MACHINED PIN XXP MALE THROUGH HOLE TIN SHELL+DIMPLE ROHS																																																															
DATE 制表日	2009/08/13	UNIT 單位 M M	PART NO.																																																															
		PAGE 張數 1 OF 1	料號 C0574-XXMAAAXXR																																																															
		REV. 版次 A																																																																
H	1	2	3	4	5	6	7	8																																																										