



MATERIALS AND FINISH
SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED
BACK SHELL TIN FINISHED
DIMPLES ON PLUG ONLY
INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,
UL 94V-0 RATED, BLACK COLOR
COAXIAL CONTACT : COPPER ALLOY Pb<1000ppm, FULL GOLD FLASH

ELECTRICAL CHARACTERISTICS
COAXIAL CONTACT IMPEDANCE : 50Ω
COAXIAL CONTACT RESISTANCE : 2.7 mΩ MAX.
INSULATION RESISTANCE : 10⁷mΩ MIN.
TEMPERATURE RATING : -55°C ~ +125°C

Tolerance ± 0.30

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	 TOLERANCE 容許公差 0 ± .00 ± ANG ±	PART NAME 品名 D-SUB COAXIAL SOLDER TYPE 3W3 MALE 50 OHMS THROUGH HOLE TIN SHELL+DIMPLE WITH SIGNAL CONTACT GOLD PLATING BLACK INSULATOR ROHS
DWG. 製圖	KAREN		
DATE 制表日	2012/07/27	UNIT 單位	M M
		PAGE 張數	1 OF 1
		REV. 版本	A
		PART NO. 料號 C0590-AMAAA0GBR	