



REMARKS:

1. MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED  
DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS  
FILLED, UL 94V-0 RATED

CONTACT MATERIAL : BRASS

CONTACT FINISH : FULL GOLD FLASH

RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED

2. ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS

CONTACT RESISTANCE : 30 MILLIOHMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.

INSULATION RESISTANCE : 5000 MEGAOHMS MIN.

TEMPERATURE RATING : -55°C ~ +105°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 IP67 D-SUB WATERPROOF TYPE 90° 9PIN FEMALE THREAD INSERT #4-40UNC NON ACCESSORIES ROW TO ROW:2.84mm GOLD FLASH PLATING TIN SHELL BLACK COLOR ROHS
DWG. 製圖	Betty	SCALE 比例 參考	PART NO. 料號 C0604-09FAATGBBR
DATE 制表日	2018/09/18	UNIT 單位 M M	
		PAGE 張數 1 OF 1	
		REV. 版次 A	