



- NOTES:**
- Electrical specifications:**
 - Contact resistance: 100mOhm max
 - Voltage rating (SELV): 15Vdc max
 - Current rating: 1A
 - Dielectric strength: 500Vrms min. 1min
 - Insulation resistance: 10E9Ohm min
 - Climatic characteristics:**
 - Operation temperature: -40°C to +85°C
 - Mechanical specifications:**
 - Contact force nominal: 20-50cn
 - Mechanical lifetime: 1,500 mating cycles min
 - Contact position acc.to GSM

RoHS Compliant		 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.													
APPD. 核准	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	<small>UNLESS OTHERWISE SPECIFIED TOLERANCES</small> <table border="1"> <tr> <th></th> <th>U.S.</th> <th>METRIC</th> </tr> <tr> <td>X</td> <td>1/16</td> <td>0.15</td> </tr> <tr> <td>XX</td> <td>1/32</td> <td>0.1</td> </tr> <tr> <td>XXX</td> <td>1/64</td> <td>0.05</td> </tr> </table>		U.S.	METRIC	X	1/16	0.15	XX	1/32	0.1	XXX	1/64	0.05	PART NAME 品名 SIM CARD SLIDE IN TYPE 6PIN SMT 90° ROW PITCH=12.0MM H=2.64MM W/O LOCATING PEG & W/O SWITCH REEL PACKING SELECTIVE GOLD 1U" ROHS
			U.S.	METRIC											
X	1/16	0.15													
XX	1/32	0.1													
XXX	1/64	0.05													
DWG. 製圖 Betty	DATE 制表日 2018/08/27	PART NO. 料號 C0610-06BEANBRR													