



Notes:
Material: Phosphor Bronze(C5191-H)
 SIMM Card Connector,With
 Cover,Type 1,8 Pin
Physical:
 Housing: LCP UL 94V-0
 Contact: Selective Gold Flash
Specifications:
 Voltage Current rating: 1A. 50V AC
 Insulation Resistance: 1000Mohm Min
 Contact Withstanding Voltage:
 AC 500V For 1 Minute
 Temperture Rating: -40° To +85°

REFERENCE PC BOAD LAYOUT

| | | | |
|------------------------|--------------------------|---|--|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 Betty | | TOLERANCE X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.° ±2° X.X° ±0.5° | PART NAME 品名 SIM CARD SLIDE IN TYPE 6PIN SMT 90° ROW PITCH:10.0mm H=2.6mm W/ SWITCH & W/O LOCATING PEG SELECTIVE GOLD PLATING REEL PACKING ROHS |
| DWG. 製圖 Betty | SCALE 比例 參考 | UNIT 單位 M M | PART NO. 料號 C0610-06BICSBRR |
| DATE 制表日 2016/08/15 | PAGE 張數 1 OF 1 | REV. 版次 A | |