



Step 1. Position of picking card out by finger

Step 2. Eject card position by groove

EJECT CARD WITH AID THROUGH THIS GROOVE

DATECODE YWWD

Step.1

Step.2

SIM CARD PIN ASSIGNMENT

PIN	ASSIGNMENT
C1	Vcc
C2	RST
C3	CLK
C5	GND
C6	Vpp
C7	I/O

RECOMMENDED LAYOUT  
GENERAL TOLERANCE: ±0.05

3	SHELL	Stainless Steel, gold flash on tail area under nickel plating
2	TERMINAL	Phosphor Bronze, 10u" selective gold under nickel plating
1	HOUSING	LCP, UL94V-0, Black
NO.	PART NAME	DESCRIPTION

**RoHS Compliant** **HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	SCALE 比例 參考	TOLERANCE DECIMAL LINEAR ANGLES X. ±0.50 ±5° X.X ±0.25 ±3° X.XX ±0.12 ±1°	PART NAME 品名 NANO SIM CARD CONNECTOR 6PIN SMT TYPE H=1.2MM GOLD FLASH PLATING WITHOUT LOCATING PEG BLACK COLOR REEL PACKING ROHS
DWG. 製圖 Hedy			
DATE 制表日 2022/07/14	PAGE 張數 1 / 1	REV. 版次 B	PART NO. 料號 C0654-06DGNBR0R