



- NOTES:**
- Material:**
Housing: hi-temperature plastic, UL94v-0;
Contact: copper alloy;
Shell: stainless steel.
 - Finish:**
Contact: gold flashed allover and nickel under-plated allover.
 - Electrical specifications:**
Contact resistance: 30m Ohm MAX.
Voltage rating (SELV): 15Vdc MAX.
Current rating: 1A
Dielectric strength: 500Vrms min. 1 MIN.
Insulation resistance: 10M Ohm MIN.
 - Climatic characteristics:**
Operation temperature: -40°C to +85°C
 - Mechanical specifications:**
Contact force nominal: 20-50cn
Mechanical lifetime: 3,000 mating cycles MIN.

PIN ASSIGNMENT TABLE:

PIN NO.	PIN NAME
C1	VCC
C2	RST
C3	CLK
C4	N/A
C5	GND
C6	VPP
C7	I/O
C8	N/A

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	 SCALE 比例 参考	UNLESS OTHERWISE SPECIFIED TOLERANCES U.S. METRIC 1/16 3/32 1/8 5/16 3/8 1/2 5/8 3/4 7/8 1 1 1/4 1 1/2 1 3/4 2 2 1/4 2 1/2 3 3 1/2 4 4 1/2 5 5 1/2 6 6 1/2 7 7 1/2 8 8 1/2 9 9 1/2 10 FRACTIONS ANGLES °/-'
DWG. 製圖	ABBY		
DATE 制表日	2018/01/25	UNIT 單位	M M
		PAGE 張數	1 OF 1
		REV. 版次	A
		PART NAME 品名	Nano SIM Card Connector Hinged Cover 6Pin SMT Type H=1.5mm Selective Gold Plating Without Locating Peg Black Color Reel Packing ROHS
		PART NO. 料號	C0655-06DSNBR0R