



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: KG MAXIMUM.
 CONTACT SEPARATION FORCE: KG MINIMUM.

MATERIALS:

CONTACT: BRASS..
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.

FINISHES:

CONTACTS:GOLD PLATED 3u",5u",10u",15u",30u".
 SHELL:NICKEL PLATED.

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2
14	43.92	35.99	25.2	15.25	11.9
24	54.71	46.79	36.0	15.25	11.9
36	67.69	59.74	48.9	15.25	11.9
50	82.78	74.85	64.0	15.25	11.9

**RoHS
Compliant**

**HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖		SCALE 比例	
DATE 制表日	Hedy	UNIT 單位	CENTRONIC SOLDER TYPE XXF SIMPLE TYPE THROUGH HOLE W/LATCH NICKEL SHELL BULE INSULATOR ROHS
2017/10/23		M M	
		PAGE 張數	PART NO.
		1 / 1	料號 C0710-XXFBAXL0R