



INSULATOR - P.B.T. +30%GLASS FIBER  
UL 94V-0

CONTACT - BRONZE

SHELL FINISH - STEEL NICKEL PLATED

HOOD - STEEL

PLATING - CONTACT

1. GOLD FLASH (COMPLETE)

2. SELECTIVE GOLD OVER NICKEL PLATED  
(CONTACT AREA) TIN OVER NICKEL PLATED (TAIL AREA)

- SHELL  
NICKEL OVER COPPER PLATED

- HOOD  
NICKEL OVER COPPER PLATED

### ELECTRICAL CHARACTERISTICS

RATING CURRENT : 5 AMP

CONTACT RESISTANCE : < 25 MILLIOHM

INSULATION RESISTANCE : > 1000 MEGOHM AT 500V

DIELECTRIC VOLTAGE : 1000V AT 1 MINUTE

OPERATION TEMPERATURE : -55°C TO +105°C

APPLIED TO WAVE SOLDER CAPABLE TO 240°

POSITION	A	B	C
14M	25.50	36.00	43.90
24M	36.30	46.80	54.70
36M	49.30	59.70	67.70
50M	64.40	74.90	82.80

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.  
核准  
Betty  
DATE 制表日  
2017/10/24

SCALE  
比例 參考  
UNIT  
單位 M M  
PAGE  
張數 1 OF 1

UNLESS OTHERWISE  
SPECIFIED TOLERANCE  
ANG.  $\pm 5^\circ$   
0.  $\pm 0.5$   
.0  $\pm 0.3$   
.00  $\pm 0.2$   
SIZE.  
紙張尺寸 A 4  
REV.  
版次 A

PART NAME 品名  
CENTRONIC SOLDER TYPE XXP MALE  
PANEL TYPE THROUGH HOLE WITHOUT LATCH  
NICKEL SHELL BULE INSULATOR ROHS

PART NO.  
料號 C0710-XXMAAXL0R