



### MATERIAL & FINISHES

- INSULATOR - P.B.T. +30%GLASS FIBER
- UL 94V-0
- CONTACT - PHOSPHOR BRONZE
- SHELL FINISH - STEEL NICKEL PLATED
- HOOD - STEEL
- PLATING - CONTACT
  - 1. GOLD FLASH (COMPLETE)
  - 2. SELECTIVE GOLD OVER NICKEL PLATED
- (CONTACT AREA) TIN OVER NICKEL PLATED (TAIL AREA)
  - SHELL
  - NICKEL OVER COPPER PLATED
  - HOOD
  - NICKEL OVER COPPER PLATED

### ELECTRICAL CHARACTERISTICS

- RATING CURRENT : 1 AMP
- CONTACT RESISTANCE : < 25 MILLIOHM
- INSULATION RESISTANCE : > 1000 MEGOHM AT 500V
- DIELECTRIC VOLTAGE : 1000V AT 1 MINUTE
- OPERATION TEMPERATURE :  $-55^{\circ}\text{C}$  TO  $+105^{\circ}\text{C}$

APPLIED TO WAVE SOLDER CAPABLE TO  $240^{\circ}$

POSITION	A	B	C
14F	25.20	36.00	43.90
24F	36.00	46.80	54.70
36F	48.90	59.70	67.70
50F	64.10	74.90	82.80

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN DWG. 製圖 ABBY DATE 制表日 2014/07/08	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 $\pm 0.3$ .00 $\pm 0.2$ ANG $\pm 5$ SIZE 紙張尺寸 A 4 REV. 次 A	PART NAME 品名 CENTRONIC PCB 90° XXF SCREW W/BOARDLOCK W/O LATCH ROHS PART NO. 料號 C0713-XXFAAXX0R