



RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: ±0.10mm

INSULATOR - P.B.T. +30%GLASS FIBER
UL 94V-0

CONTACT - PHOSPHOR BRONZE
SHELL FINISH - STEEL NICKEL PLATED

HOOD - STEEL
PLATING - CONTACT

1. GOLD FLASH (COMPLETE)
2. SELECTIVE GOLD OVER NICKEL PLATED
(CONTACT AREA) TIN OVER NICKEL PLATED (TAIL AREA)
- SHELL
NICKEL OVER COPPER PLATED
- HOOD
NICKEL OVER COPPER PLATED

ELECTRICAL CHARACTERISTICS

RATING CURRENT : 1 AMP
CONTACT RESISTANCE : < 25 MILLIOHM
INSULATION RESISTANCE : > 1000 MEGOHM AT 500V
DIELECTRIC VOLTAGE : 1000VAC AT 1 MINUTE
OPERATION TEMPERATURE : -55°C TO +105°C

APPLIED TO WAVE SOLDER CAPABLE TO 240°

POSITION	A	B	C
14M	25.50	36.00	43.90
24M	36.30	46.80	54.70
36M	49.30	59.70	67.70
50M	64.40	74.90	82.80

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
DWG. 製圖
DATE 制表日
2016/08/16

SCALE 比例 參考
UNIT 單位 M M
PAGE 張數 1 OF 1

PART NAME 品名
CENTRONIC PCB 90° XXPIN MALE
FIX SCREW WITH L-SHAPE
(WITH 4-40UNC) WITHOUT LATCH ROHS
PART NO.
料號 C0713-XXMACXX0R