



MATERIAL & FINISHES

- INSULATOR - P.B.T. +30%GLASS FIBER
- UL 94V-0
- CONTACT - PHOSPHOR BRONZE
- SHELL FINISH - STEEL NICKEL PLATED
- HOOD - STEEL
- PLATING - CONTACT
 - 1. GOLD FLASH (COMPLETE)
 - 2. SELECTIVE GOLD OVER NICKEL PLATED
- (CONTACT AREA) TIN OVER NICKEL PLATED (TAIL AREA)
 - SHELL
 - NICKEL OVER COPPER PLATED
 - HOOD
 - NICKEL OVER COPPER PLATED

ELECTRICAL CHARACTERISTICS

- RATING CURRENT : 5 AMP
- CONTACT RESISTANCE : < 25 MILLIOHM
- INSULATION RESISTANCE : > 1000 MEGOHM AT 500V
- DIELECTRIC VOLTAGE : 1000V AT 1 MINUTE
- OPERATION TEMPERATURE : -55°C TO +105°C

APPLIED TO WAVE SOLDER CAPABLE TO 240°

POSITION	A	B	C	D
14M	25.50	29.40	38.50	6
24M	36.30	40.20	49.30	11
36M	49.30	53.50	62.00	17
50M	64.40	68.30	77.40	24

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. ±5° 0. ±0.5 .0 ±0.3 .00 ±0.2	PART NAME 品名 CENTRONIC PCB RIGHT ANGEL TYPE XXPIN MALE WITH NOTCH EAR WITHOUT LATCH NICKEL SHELL BLUE COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C0713-XXMC0SL0R
DATE 制表日 2016/10/19	PAGE 張數 1 OF 1	REV. 版次 A	