



MATERIALS:
 PLASTIC HOUSING:
 ENGINEERING THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.

COLOUR: WHITE.
CONTACTS: PHOSPHOR BRONZE.
PLATING: TIN PLATING OVER NICKEL.

ELECTRICAL:
 VOLTAGE: 125VAC
 CURRENT: 1.0A
 CONTACT RESISTANCE: 20mOhms Max.
 INSULATION RESISTANCE: 1000MOhms Min.
 DIELECTRIC WITHSTANDING VOLTAGE: 500VAC
 WIRING: ACCOMODATES 24 & 26 AWG.

ENVIRONMENTAL:
 OPERATING TEMPERATURE: -40°C ~ +85°C
 STORAGE TEMPERATURE: -40°C ~ +85°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 3.81mm IDC BLOCK 8P FOR 110 TYPE PHOSPHOR BRANZE TIN PLATING WITH PROTRUDE POST PRINT: BROWN, GREEN, ORANGE, BLUE COLOR BEIGE INSULATOR ROHS
DWG. 製圖 <i>Helen</i>	SCALE 比例 參考	0 ± 0.35 .00 ± 0.25 ANG. ± 3°	PART NO. 料號 C0802-08APTIYBR
DATE 制表日 2020/7/30	UNIT 單位 MM	SIZE. 紙張尺寸 A4	
	PAGE 張數 1 OF 1	REV. 版本 A	