



NOTES 1:

- UL Standard :
- 1.Rating: 300V 8A
 - 2.Insulation Withstands Voltage: AC 2000 V at 1 minute
 - 3.Using Temperature Range: -40°C~+115°C
- IEC Standard:
1. Rating: 320V 14A
 2. Rate Impulse Voltage: 2500V
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Material Group : I
 5. Pollution Degree : 2
 6. Overtoltage Category: II
 7. Using Temperature Range: -40°C~+110°C

2	SOLDER PIN	COPPER ALLOY	Tin Plated
1	HOUSING	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

P	2	3	4	5	6	7	8	9	10	11	12	
U	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.1	41.91	
P	13	14	15	16	17	18	19	20	21	22	23	24
U	45.72	49.53	53.34	57.15	60.96	64.77	68.58	72.39	76.2	80.01	83.82	87.63

P.C.B. LAYOUT
S=3:1

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	SCALE 比例 參考	.0 ±	3.81mm P.C.B. TERMINAL BLOCK RIGHT ANGLE TYPE XXPIN WITHOUT EAR TIN PLATED GREEN INSULATOR ROHS
DATE 制表日	UNIT 單位	.00 ±	
2018/11/21	PAGE 張數	ANG. ±	PART NO. 料號
	1 OF 1	SIZE. 紙張尺寸	C0913-XXRNTE00R
		A 4	
		REV. 版次	
		B	